

Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade

Winchester Australia Ltd

Chemwatch Hazard Alert Code: 4

Chemwatch: 5218-81

Issue Date: 05/03/2017

Version No: 3.1.1.1

Print Date: 20/06/2019

Safety Data Sheet according to WHS and ADG requirements

L.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

| | |
|-------------------------------|--|
| Product name | Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade |
| Synonyms | Not Available |
| Proper shipping name | AMMUNITION, SMOKE with or without burster, expelling charge or propelling charge |
| Other means of identification | Not Available |

Relevant identified uses of the substance or mixture and uses advised against

| | |
|--------------------------|---|
| Relevant identified uses | Use according to manufacturer's directions. Explosive product. |
|--------------------------|---|

Details of the supplier of the safety data sheet

| | |
|-------------------------|---|
| Registered company name | Winchester Australia Ltd |
| Address | 65 Hays Road Moolap, Geelong VIC 3224 Australia |
| Telephone | +61 3 5245 2400 |
| Fax | +61 3 5248 2409 |
| Website | Not Available |
| Email | aedmondson@olin.com.au |

Emergency telephone number

| | |
|-----------------------------------|--------------------------|
| Association / Organisation | Winchester Australia Ltd |
| Emergency telephone numbers | 0418 158 337 All hours |
| Other emergency telephone numbers | Not Available |

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.


CHEMWATCH HAZARD RATINGS

| | Min | Max |
|--------------|-----|-----|
| Flammability | 1 | |
| Toxicity | 0 | |
| Body Contact | 1 | |
| Reactivity | 4 | |
| Chronic | 0 | |

0 = Minimum
1 = Low
2 = Moderate
3 = High
4 = Extreme

| | |
|-------------------------------|---|
| Poisons Schedule | Not Applicable |
| Classification ^[1] | Explosive Division 1.4, Self Reactive Type A |
| Legend: | 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI |

Label elements

| | |
|---------------------|---|
| Hazard pictogram(s) |  |
|---------------------|---|

SIGNAL WORD **DANGER**

Hazard statement(s)

| | |
|------|---------------------------------|
| H204 | Fire or projection hazard. |
| H240 | Heating may cause an explosion. |

Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade

Precautionary statement(s) Prevention

| | |
|------|--|
| P210 | Keep away from heat/sparks/open flames/hot surfaces. - No smoking. |
| P234 | Keep only in original container. |
| P250 | Do not subject to grinding/shock/sources of friction. |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection. |
| P220 | Keep/Store away from clothing/organic material/combustible materials. |
| P240 | Ground/bond container and receiving equipment. |

Precautionary statement(s) Response

| | |
|----------------|---|
| P370+P380 | In case of fire: Evacuate area. |
| P370+P380+P375 | In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. |
| P372 | Explosion risk in case of fire. |
| P374 | Fight fire with normal precautions from a reasonable distance. |
| P373 | DO NOT fight fire when fire reaches explosives. |
| P370+P378 | In case of fire: Use water spray/fog for extinction. |

Precautionary statement(s) Storage

| | |
|-----------|--|
| P403+P235 | Store in a well-ventilated place. Keep cool. |
| P411 | Store at temperatures not exceeding 30°C/86°F (see storage requirements on SDS). |
| P401 | Store according to local regulations for explosives. |
| P420 | Store away from other materials. |

Precautionary statement(s) Disposal

| | |
|------|---|
| P501 | Dispose of contents/container in accordance with local regulations. |
|------|---|

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

| CAS No | %[weight] | Name |
|-----------|-----------|--------------------------------------|
| 84-65-1 | 25-50 | <u>9,10-anthraquinone</u> |
| 3811-04-9 | 25-50 | <u>potassium chlorate</u> |
| 57-50-1 | 10-25 | <u>sucrose</u> |
| 7760-50-1 | <10 | <u>magnesium carbonate hydroxide</u> |
| 7757-79-1 | <10 | <u>potassium nitrate</u> |
| 7440-21-3 | <10 | <u>silicon</u> |
| 9004-70-0 | <10 | <u>nitrocellulose</u> |
| 67-64-1 | <10 | <u>acetone</u> |
| 7440-02-0 | <10 | <u>nickel</u> |

SECTION 4 FIRST AID MEASURES

Description of first aid measures

| | |
|---------------------|---|
| Eye Contact | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Wash out immediately with fresh running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Seek medical attention without delay; if pain persists or recurs seek medical attention. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. |
| Skin Contact | <p>If skin contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately remove all contaminated clothing, including footwear. ▶ Flush skin and hair with running water (and soap if available). ▶ Seek medical attention in event of irritation. |
| Inhalation | <ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor. |
| Ingestion | <ul style="list-style-type: none"> ▶ Not considered a normal route of entry. |

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ **WARNING:** Deliver water spray or fog from a safe distance only.

Special hazards arising from the substrate or mixture

| | |
|-----------------------------|-------------|
| Fire Incompatibility | None known. |
|-----------------------------|-------------|

Advice for firefighters

| | |
|------------------------------|--|
| Fire Fighting | <p>WARNING: EXPLOSIVE MATERIALS / ARTICLES PRESENT!</p> <ul style="list-style-type: none"> ▶ Evacuate all personnel and move upwind. ▶ Prevent re-entry. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May detonate and burning material may be propelled from fire. ▶ Wear full-body protective clothing with breathing apparatus. ▶ Prevent, by any means available, spillage and fire effluent from entering drains and water courses. ▶ Fight fire from safe distances and from protected locations. ▶ Use flooding quantities of water. ▶ DO NOT approach containers or packages suspected to be hot. ▶ Cool any exposed containers not involved in fire from a protected location. ▶ Equipment should be thoroughly decontaminated after use. |
| Fire/Explosion Hazard | <p>Division 1.4 Substances, mixtures and articles which present no significant hazard: substances, mixtures and articles which present only a small hazard in the event of ignition or initiation. The effects are largely confined to the package and no projection of fragments of appreciable size or range is to be expected. An external fire shall not cause virtually instantaneous explosion of almost the entire contents of the package.</p> <p>Compatibility Group G explosives are pyrotechnic substances, or article containing a pyrotechnic substances, or article containing both an explosive substance and an illuminating, incendiary, tear- or smoke-producing substance (other than a water-activated article or one containing white phosphorus, phosphides, a pyrophoric substance, a flammable liquid or gel, or hypergolic liquids).</p> <p>Decomposes on heating and produces toxic fumes of: carbon monoxide (CO) carbon dioxide (CO₂) nitrogen oxides (NO_x) metal oxides</p> <p>[Individual items may explode. Mass explosion of many items at once is unlikely;]In unusual cases, shrapnel may be thrown from exploding devices under containment</p> |
| HAZCHEM | 1YE |

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

| | |
|---------------------|---|
| Minor Spills | <p>WARNING!: EXPLOSIVE.</p> <p>BLAST and/or PROJECTION and/or FIRE HAZARD</p> <ul style="list-style-type: none"> ▶ Clean up all spills immediately. ▶ Avoid inhalation of the material and avoid contact with eyes and skin. ▶ Wear impervious gloves and safety glasses. ▶ Remove all ignition sources. ▶ Use spark-free tools when handling. ▶ Sweep into non-sparking containers or barrels and moisten with water. ▶ Place spilled material in clean, sealable, labelled container for disposal. ▶ Flush area with large amounts of water. |
| Major Spills | <p>WARNING! EXPLOSIVE.</p> <ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. ▶ Wear full body protective clothing with breathing apparatus. ▶ Consider evacuation (or protect in place). ▶ In case of transport accident notify Police, Emergency Authority, Competent Explosives Authority or Manufacturer. ▶ No smoking, naked lights, heat or ignition sources. ▶ Increase ventilation. ▶ Use extreme caution to prevent physical shock. ▶ Use only spark-free shovels and explosion-proof equipment. ▶ Collect recoverable material and segregate from spilled material. ▶ Wash spill area with large quantities of water. |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

| | |
|----------------------|---|
| Safe handling | <ul style="list-style-type: none"> ▶ Handle gently. Use good occupational work practice. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. |
|----------------------|---|

Continued...

Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade

| | |
|--------------------------|--|
| | <ul style="list-style-type: none"> ▶ Avoid all personal contact, including inhalation. ▶ Avoid smoking, naked lights, heat or ignition sources. ▶ Explosives must not be struck with metal implements. ▶ Avoid mechanical and thermal shock and friction. ▶ Use in a well ventilated area. ▶ Avoid contact with incompatible materials. ▶ When handling DO NOT eat, drink or smoke. ▶ Avoid physical damage to containers. ▶ Always wash hands with soap and water after handling. ▶ Work clothes should be laundered separately. |
| Other information | <ul style="list-style-type: none"> ▶ Store cases in a well ventilated magazine licensed for the appropriate Class, Division and Compatibility Group. ▶ Rotate stock to prevent ageing. Use on FIFO (first in-first out) basis. ▶ Observe manufacturer's storage and handling recommendations contained within this SDS. ▶ Store in a cool place in original containers. ▶ Keep containers securely sealed. ▶ No smoking, naked lights, heat or ignition sources. ▶ Store in an isolated area away from other materials. ▶ Keep storage area free of debris, waste and combustibles. ▶ Protect containers against physical damage. ▶ Check regularly for spills and leaks <p>NOTE: If explosives need to be destroyed contact the Competent Authority.</p> |

Conditions for safe storage, including any incompatibilities

| | |
|--------------------------------|--|
| Suitable container | <ul style="list-style-type: none"> ▶ All packaging for Class 1 Goods shall be in accordance with the requirements of the relevant Code for the transport of Dangerous Goods. ▶ Class 1 is unique in that the type of packaging used frequently has a very decisive effect on the hazard and therefore on the assignment to a particular division |
| Storage incompatibility | <ul style="list-style-type: none"> ▶ Avoid storage with reducing agents. ▶ Contact with acids produces toxic fumes ▶ Avoid any contamination of this material as it is very reactive and any contamination is potentially hazardous ▶ Explosion hazard may follow contact with incompatible materials ▶ Avoid reaction with oxidising agents ▶ Avoid strong acids, acid chlorides, acid anhydrides and chloroformates. <p>strong alkalis</p> |



X + X X X X X X

X — Must not be stored together
0 — May be stored together with specific preventions
+ — May be stored together

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

| Source | Ingredient | Material name | TWA | STEL | Peak | Notes |
|------------------------------|------------|----------------|----------------------|-----------------------|---------------|--|
| Australia Exposure Standards | sucrose | Sucrose | 10 mg/m3 | Not Available | Not Available | (a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica. |
| Australia Exposure Standards | silicon | Silicon | 10 mg/m3 | Not Available | Not Available | (a) This value is for inhalable dust containing no asbestos and < 1% crystalline silica. |
| Australia Exposure Standards | acetone | Acetone | 500 ppm / 1185 mg/m3 | 2375 mg/m3 / 1000 ppm | Not Available | Not Available |
| Australia Exposure Standards | nickel | Nickel, metal | 1 mg/m3 | Not Available | Not Available | Not Available |
| Australia Exposure Standards | nickel | Nickel, powder | 1 mg/m3 | Not Available | Not Available | Not Available |

EMERGENCY LIMITS

| Ingredient | Material name | TEEL-1 | TEEL-2 | TEEL-3 |
|-------------------------------|-------------------------------|---------------|---------------|---------------|
| 9,10-anthraquinone | Anthraquinone | 0.87 mg/m3 | 9.6 mg/m3 | 57 mg/m3 |
| potassium chlorate | Potassium chlorate | 5.6 mg/m3 | 62 mg/m3 | 370 mg/m3 |
| magnesium carbonate hydroxide | Magnesium carbonate hydroxide | 30 mg/m3 | 330 mg/m3 | 2,000 mg/m3 |
| potassium nitrate | Potassium nitrate | 9 mg/m3 | 100 mg/m3 | 600 mg/m3 |
| silicon | Silicon | 45 mg/m3 | 100 mg/m3 | 630 mg/m3 |
| acetone | Acetone | Not Available | Not Available | Not Available |
| nickel | Nickel | 4.5 mg/m3 | 50 mg/m3 | 99 mg/m3 |


| Ingredient | Original IDLH | Revised IDLH |
|--------------------|---------------|---------------|
| 9,10-anthraquinone | Not Available | Not Available |
| potassium chlorate | Not Available | Not Available |

Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade

| | | |
|-------------------------------|---------------|---------------|
| sucrose | Not Available | Not Available |
| magnesium carbonate hydroxide | Not Available | Not Available |
| potassium nitrate | Not Available | Not Available |
| silicon | Not Available | Not Available |
| nitrocellulose | Not Available | Not Available |
| acetone | 2,500 ppm | Not Available |
| nickel | Not Available | Not Available |

MATERIAL DATA

Exposure controls

| | |
|---|--|
| Appropriate engineering controls | <p>Engineering controls for explosive articles are designed to reduce or eliminate fragmentation and/or blast effects either by suppression of the source of detonation or by protection at the exposed location, or both. Barricades, shields, contained detonation chambers, and "zero quantity-distance (Q-D)" magazines are examples of engineering controls.</p> <p>Engineering controls are designed and tested in a rigorous fashion. The construction of the engineering control must be carefully duplicated in field applications to assure it will function properly.</p> <p>It is thus imperative that engineering controls be built exactly in accordance with the design package, and that they be used only for the articles (e.g.munitions) for which they are authorised.</p> |
| Personal protection |  |
| Eye and face protection | <ul style="list-style-type: none"> ▶ Safety glasses. ▶ Safety glasses with side shields. ▶ Chemical goggles. ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59], [AS/NZS 1336 or national equivalent] |
| Skin protection | See Hand protection below |
| Hands/feet protection | <p>Wear physical protective gloves, e.g. leather</p> <ul style="list-style-type: none"> ▶ Heavy weight Rubber gloves <ul style="list-style-type: none"> • Non-sparking or conductive footwear essential. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return. ▶ Rubber boots |
| Body protection | See Other protection below |
| Other protection | <p>For handling explosives or explosive compositions:</p> <ul style="list-style-type: none"> ▶ Wear close-fitting flame-protection treated clothing closed at the neck and sleeves. ▶ Cotton underwear, socks and conductive shoes are recommended to avoid human static discharge. |

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade

| Material | CPI |
|------------------|-----|
| BUTYL | C |
| BUTYL/NEOPRENE | C |
| CPE | C |
| HYPALON | C |
| NATURAL RUBBER | C |
| NATURAL+NEOPRENE | C |
| NEOPRENE | C |
| NITRILE | C |
| NITRILE+PVC | C |
| PE/EVAL/PE | C |
| PVA | C |
| PVC | C |
| PVDC/PE/PVDC | C |
| SARANEX-23 | C |
| SARANEX-23 2-PLY | C |

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES | AX-AUS | - | AX-PAPR-AUS / Class 1 |
| up to 50 x ES | - | AX-AUS / Class 1 | - |
| up to 100 x ES | - | AX-2 | AX-PAPR-2 ^ |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

7part

Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade

| | |
|----------------|---|
| TEFLON | C |
| VITON/NEOPRENE | C |

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

| | | | |
|---|---|--|----------------|
| Appearance | Grey odourless solid, insoluble in water. | | |
| Physical state | Manufactured | Relative density (Water = 1) | Not Available |
| Odour | Not Available | Partition coefficient n-octanol / water | Not Available |
| Odour threshold | Not Available | Auto-ignition temperature (°C) | Not Available |
| pH (as supplied) | Not Applicable | Decomposition temperature | Not Available |
| Melting point / freezing point (°C) | Not Available | Viscosity (cSt) | Not Applicable |
| Initial boiling point and boiling range (°C) | Not Available | Molecular weight (g/mol) | Not Applicable |
| Flash point (°C) | Not Applicable | Taste | Not Available |
| Evaporation rate | Not Applicable | Explosive properties | Not Available |
| Flammability | Not Applicable | Oxidising properties | Not Available |
| Upper Explosive Limit (%) | Not Available | Surface Tension (dyn/cm or mN/m) | Not Applicable |
| Lower Explosive Limit (%) | Not Available | Volatile Component (%vol) | Not Available |
| Vapour pressure (kPa) | Not Applicable | Gas group | Not Available |
| Solubility in water | Immiscible | pH as a solution (1%) | Not Available |
| Vapour density (Air = 1) | Not Applicable | VOC g/L | Not Available |

SECTION 10 STABILITY AND REACTIVITY

| | |
|---|---|
| Reactivity | See section 7 |
| Chemical stability | <ul style="list-style-type: none"> ▶ Presence of elevated temperatures. • Unstable in the presence of incompatible materials ▶ Presence of shock and friction ▶ Presence of heat source and ignition source Avoid contact with other chemicals. |
| Possibility of hazardous reactions | See section 7 |
| Conditions to avoid | See section 7 |
| Incompatible materials | See section 7 |
| Hazardous decomposition products | See section 5 |

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

| | |
|---------------------|--|
| Inhaled | Not normally a hazard due to physical form of product. Irritating to respiratory system. |
| Ingestion | Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Not normally a hazard due to physical form of product. |
| Skin Contact | Not normally a hazard due to physical form of product. Limited evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period. Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis. |
| Eye | Limited evidence exists, or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals and/or is expected to produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur. |

Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade

| | | |
|---|--|------------------------------------|
| | Not normally a hazard due to physical form of product. | |
| Chronic | <p>Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.</p> <p>Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.</p> <p>[Explosive components are completely sealed within the container. Under normal handling of this product, no exposure to harmful materials will occur. Product may produce physical injury if mishandled. Treatment of these injuries should be based on the blast and compression effects.</p> | |
| Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade | TOXICITY | |
| | Not Available | |
| | IRRITATION | |
| | Not Available | |
| 9,10-anthraquinone | TOXICITY | |
| | dermal (rat) LD50: >500 mg/kg ^[2] | |
| | Inhalation (rat) LC50: >1.3 mg/l/4H ^[2] | |
| | Oral (rat) LD50: >2000 mg/kg ^[1] | |
| | IRRITATION | |
| | Eye (rabbit): not irritating * | |
| | Sin (rabbit): not irritating * | |
| potassium chlorate | TOXICITY | |
| | dermal (rat) LD50: >2000 mg/kg ^[1] | |
| | Oral (rat) LD50: 1870 mg/kg ^[2] | |
| sucrose | TOXICITY | |
| | Oral (rat) LD50: 29700 mg/kg ^[2] | |
| magnesium carbonate hydroxide | TOXICITY | |
| | Not Available | |
| potassium nitrate | TOXICITY | |
| | dermal (rat) LD50: >5000 mg/kg ^[1] | |
| | Oral (rat) LD50: >2000 mg/kg ^[1] | |
| silicon | TOXICITY | |
| | Oral (rat) LD50: >50-300 mg/kg ^[1] | |
| | IRRITATION | |
| | Eye: no adverse effect observed (not irritating) ^[1] | |
| | Skin: no adverse effect observed (not irritating) ^[1] | |
| nitrocellulose | TOXICITY | |
| | Oral (rat) LD50: >5000 mg/kg ^[2] | |
| | IRRITATION | |
| | Not Available | |
| acetone | TOXICITY | |
| | Dermal (rabbit) LD50: =20 mg/kg ^[2] | |
| | Inhalation (rat) LC50: 100.2 mg/l/8hr ^[2] | |
| | Oral (rat) LD50: 1800-7300 mg/kg ^[2] | |
| | | Eye (human): 500 ppm - irritant |
| | | Eye (rabbit): 20mg/24hr - moderate |
| | Eye (rabbit): 3.95 mg - SEVERE | |
| | Eye: adverse effect observed (irritating) ^[1] | |
| | Skin (rabbit): 500 mg/24hr - mild | |
| | Skin (rabbit): 395mg (open) - mild | |
| | Skin: no adverse effect observed (not irritating) ^[1] | |
| nickel | TOXICITY | |
| | Oral (rat) LD50: 5000 mg/kg ^[2] | |
| | IRRITATION | |
| | Eye: no adverse effect observed (not irritating) ^[1] | |
| | Skin: no adverse effect observed (not irritating) ^[1] | |
| Legend: | 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances | |
| SUCROSE | Oral (Human) TDLo: 9.6E-5 mg/kg | |
| SILICON | <p>Intraperitoneal injection of silicon produced only minor local trauma and foreign body reaction. Parenterally administered elemental silica is considered biologically inert.</p> <p>Dogs and rats fed 800 mg silicon/kg/day (as the dioxide) for 1 month showed no clinical signs or histological changes.</p> <p>The compound was largely eliminated in the faeces.</p> <p>Normal human cerebral cortex tissue contains about 3.8 ug/g silicon</p> <p>The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> | |
| ACETONE | The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. | |

| | |
|--|---|
| | <p>for acetone:</p> <p>The acute toxicity of acetone is low. Acetone is not a skin irritant or sensitiser but is a defatting agent to the skin. Acetone is an eye irritant. The subchronic toxicity of acetone has been examined in mice and rats that were administered acetone in the drinking water and again in rats treated by oral gavage. Acetone-induced increases in relative kidney weight changes were observed in male and female rats used in the oral 13-week study. Acetone treatment caused increases in the relative liver weight in male and female rats that were not associated with histopathologic effects and the effects may have been associated with microsomal enzyme induction. Haematologic effects consistent with macrocytic anaemia were also noted in male rats along with hyperpigmentation in the spleen. The most notable findings in the mice were increased liver and decreased spleen weights. Overall, the no-observed-effect-levels in the drinking water study were 1% for male rats (900 mg/kg/d) and male mice (2258 mg/kg/d), 2% for female mice (5945 mg/kg/d), and 5% for female rats (3100 mg/kg/d). For developmental effects, a statistically significant reduction in foetal weight, and a slight, but statistically significant increase in the percent incidence of later resorptions were seen in mice at 15,665 mg/m3 and in rats at 26,100 mg/m3. The no-observable-effect level for developmental toxicity was determined to be 5220 mg/m3 for both rats and mice.</p> <p>Teratogenic effects were not observed in rats and mice tested at 26,110 and 15,665 mg/m3, respectively. Lifetime dermal carcinogenicity studies in mice treated with up to 0.2 mL of acetone did not reveal any increase in organ tumor incidence relative to untreated control animals.</p> <p>The scientific literature contains many different studies that have measured either the neurobehavioural performance or neurophysiological response of humans exposed to acetone. Effect levels ranging from about 600 to greater than 2375 mg/m3 have been reported. Neurobehavioral studies with acetone-exposed employees have recently shown that 8-hr exposures in excess of 2375 mg/m3 were not associated with any dose-related changes in response time, vigilance, or digit span scores. Clinical case studies, controlled human volunteer studies, animal research, and occupational field evaluations all indicate that the NOAEL for this effect is 2375 mg/m3 or greater.</p> |
| NICKEL | <p>Tenth Annual Report on Carcinogens: Substance anticipated to be Carcinogen <i>[National Toxicology Program: U.S. Dep. of Health & Human Services 2002]</i> Oral (rat) TDL: 500 mg/kg/5D-1 Inhalation (rat) TCL: 0.1 mg/m3/24H/17W-C</p> |
| 9,10-ANTHRAQUINONE & NICKEL | <p>The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested.</p> <p>WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.</p> |
| 9,10-ANTHRAQUINONE & SILICON | <p>Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.</p> |
| MAGNESIUM CARBONATE HYDROXIDE & SILICON & NITROCELLULOSE | <p>No significant acute toxicological data identified in literature search.</p> |

| | | | |
|-----------------------------------|---|--------------------------|---|
| Acute Toxicity | ✗ | Carcinogenicity | ✗ |
| Skin Irritation/Corrosion | ✗ | Reproductivity | ✗ |
| Serious Eye Damage/Irritation | ✗ | STOT - Single Exposure | ✗ |
| Respiratory or Skin sensitisation | ✗ | STOT - Repeated Exposure | ✗ |
| Mutagenicity | ✗ | Aspiration Hazard | ✗ |

Legend: ✗ – Data either not available or does not fill the criteria for classification
 ✓ – Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

| Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade | ENDPOINT | TEST DURATION (HR) | SPECIES | VALUE | SOURCE |
|--|---------------|--------------------|---------------|---------------|---------------|
| | Not Available | Not Available | Not Available | Not Available | Not Available |

| 9,10-anthraquinone | ENDPOINT | TEST DURATION (HR) | SPECIES | VALUE | SOURCE |
|--------------------|----------|--------------------|-------------------------------|------------|--------|
| | LC50 | 96 | Fish | >0.045mg/L | 2 |
| | EC50 | 48 | Crustacea | >0.048mg/L | 2 |
| | EC50 | 72 | Algae or other aquatic plants | >0.035mg/L | 2 |
| | NOEC | 72 | Algae or other aquatic plants | 0.035mg/L | 2 |

| potassium chlorate | ENDPOINT | TEST DURATION (HR) | SPECIES | VALUE | SOURCE |
|--------------------|----------|--------------------|-------------------------------|----------|--------|
| | LC50 | 96 | Fish | >1-mg/L | 2 |
| | EC50 | 48 | Crustacea | >1-mg/L | 2 |
| | EC50 | 72 | Algae or other aquatic plants | >1-mg/L | 2 |
| | EC10 | 72 | Algae or other aquatic plants | >1-mg/L | 2 |
| | NOEC | 72 | Algae or other aquatic plants | <0.5mg/L | 4 |

Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade

| | ENDPOINT | TEST DURATION (HR) | SPECIES | VALUE | SOURCE |
|-------------------------------|---------------|--------------------|-------------------------------|------------------|---------------|
| sucrose | LC50 | 96 | Fish | 2200000mg/L | 3 |
| | EC50 | 96 | Algae or other aquatic plants | 6020000mg/L | 3 |
| magnesium carbonate hydroxide | Not Available | Not Available | Not Available | Not Available | Not Available |
| | | | | | |
| potassium nitrate | LC50 | 96 | Fish | 1-378mg/L | 2 |
| | EC50 | 48 | Crustacea | 490mg/L | 2 |
| | EC50 | 96 | Algae or other aquatic plants | 1181.887mg/L | 3 |
| | NOEC | 720 | Fish | 58mg/L | 2 |
| silicon | EC50 | 48 | Crustacea | ca.35.4mg/L | 2 |
| | EC50 | 72 | Algae or other aquatic plants | >100mg/L | 2 |
| | NOEC | 72 | Algae or other aquatic plants | ca.3.2mg/L | 2 |
| nitrocellulose | EC50 | 96 | Algae or other aquatic plants | 579mg/L | 4 |
| | | | | | |
| acetone | LC50 | 96 | Fish | 5-540mg/L | 2 |
| | EC50 | 48 | Crustacea | >100mg/L | 4 |
| | EC50 | 96 | Algae or other aquatic plants | 20.565mg/L | 4 |
| | NOEC | 240 | Crustacea | 1-866mg/L | 2 |
| nickel | LC50 | 96 | Fish | 0.0000475mg/L | 4 |
| | EC50 | 48 | Crustacea | 0.001-0.576mg/L | 2 |
| | EC50 | 72 | Algae or other aquatic plants | 0.00094mg/L | 2 |
| | BCF | 1440 | Algae or other aquatic plants | 0.47mg/L | 4 |
| | NOEC | 240 | Crustacea | >0.001-0.715mg/L | 2 |

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
DO NOT discharge into sewer or waterways.

Persistence and degradability

| Ingredient | Persistence: Water/Soil | Persistence: Air |
|--------------------|---------------------------|----------------------------------|
| 9,10-anthraquinone | HIGH | HIGH |
| potassium chlorate | HIGH | HIGH |
| sucrose | LOW | LOW |
| potassium nitrate | LOW | LOW |
| acetone | LOW (Half-life = 14 days) | MEDIUM (Half-life = 116.25 days) |

Bioaccumulative potential

| Ingredient | Bioaccumulation |
|--------------------|------------------------|
| 9,10-anthraquinone | LOW (LogKOW = 3.39) |
| potassium chlorate | LOW (LogKOW = -4.6296) |
| sucrose | LOW (LogKOW = -3.7) |
| potassium nitrate | LOW (LogKOW = 0.209) |
| acetone | LOW (BCF = 0.69) |

Mobility in soil

| Ingredient | Mobility |
|--------------------|-------------------|
| 9,10-anthraquinone | LOW (KOC = 185.7) |
| potassium chlorate | LOW (KOC = 35.04) |
| sucrose | LOW (KOC = 10) |

Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade

| | |
|-------------------|--------------------|
| potassium nitrate | LOW (KOC = 14.3) |
| acetone | HIGH (KOC = 1.981) |

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

| | |
|------------------------------|---|
| Product / Packaging disposal | <ul style="list-style-type: none"> ▶ Explosives which are surplus, deteriorated or considered unsafe for transport, storage or use shall be destroyed and the statutory authorities shall be notified. ▶ Explosives must not be thrown away, buried, discarded or placed with garbage. ▶ This material may be disposed of by burning or detonation but the operation must be performed under the control of a person competent in the destruction of explosives. <p>Disposal by detonation:</p> <ul style="list-style-type: none"> ▶ The explosives to be destroyed must be placed in direct contact with fresh priming charge in a hole which is at least 0.6 metre deep and then adequately stemmed. ▶ No detonators shall be inserted into defective explosives. ▶ Personnel must be evacuated to a safe distance prior to initiation/firing of the charge. <p>Disposal by burning:</p> <ul style="list-style-type: none"> ▶ Make a sawdust bed or trail adequate for the quantity of explosives to be burned, approximately 400 mm wide and 40 mm deep, upon which the explosive will be laid. ▶ If sawdust is not available, newspaper may be used. ▶ Normal precautions shall be taken to avoid the spread of fire. ▶ Individual trails should not be closer together than 600 mm and should contain not more than 12 kg of explosive. ▶ Trails should be side by side, NOT in-line, and not more than four should be set up at one time. ▶ Remove any explosive that is not to be burnt to a distance of at least 300 metre. ▶ Sufficient diesel oil (never petrol or other highly flammable liquid) should be used to thoroughly wet the sawdust (or paper) at least 4 litre per trail is recommended. ▶ Light the trail from a long, rolled paper wick which should be placed downwind and in contact with the end 1m of trail that is not covered with explosive. The wind should blow so that the flame from the wick (and later from the burning explosive) will blow away from the unburned explosive as detonation is more likely to occur if the explosive is preheated by the flame. ▶ If plastic igniter cord (slow) is available, its use for lighting is recommended instead of paper. One end should be coiled into the sawdust or under the paper and the other end lit from a minimum distance of 7m from the trail. ▶ Retire at least 300m or to a safe place. ▶ DO NOT return to the site for at least 30 minutes after the burning has apparently finished. ▶ If the fire goes out do not approach for at least 15 minutes after all trace of fire has gone. ▶ DO NOT add more diesel oil unless certain that the flame is completely extinguished. <p>[DYNO]</p> |
|------------------------------|---|

SECTION 14 TRANSPORT INFORMATION

Labels Required

| | |
|------------------|---|
| |  |
| Marine Pollutant | NO |
| HAZCHEM | 1YE |

Land transport (ADG)

| | | | | | |
|------------------------------|--|--------------------|------|------------------|----------------|
| UN number | 0303 | | | | |
| UN proper shipping name | AMMUNITION, SMOKE with or without burster, expelling charge or propelling charge | | | | |
| Transport hazard class(es) | <table border="0"> <tr> <td>Class</td> <td>1.4G</td> </tr> <tr> <td>Subrisk</td> <td>Not Applicable</td> </tr> </table> | Class | 1.4G | Subrisk | Not Applicable |
| Class | 1.4G | | | | |
| Subrisk | Not Applicable | | | | |
| Packing group | Not Applicable | | | | |
| Environmental hazard | Not Applicable | | | | |
| Special precautions for user | <table border="0"> <tr> <td>Special provisions</td> <td>204</td> </tr> <tr> <td>Limited quantity</td> <td>Not Applicable</td> </tr> </table> | Special provisions | 204 | Limited quantity | Not Applicable |
| Special provisions | 204 | | | | |
| Limited quantity | Not Applicable | | | | |

Air transport (ICAO-IATA / DGR)

| | | | | | | | |
|----------------------------|--|-----------------|------|---------------------|----------------|----------|----|
| UN number | 0303 | | | | | | |
| UN proper shipping name | Ammunition, smoke with or without burster, expelling charge or propelling charge | | | | | | |
| Transport hazard class(es) | <table border="0"> <tr> <td>ICAO/IATA Class</td> <td>1.4G</td> </tr> <tr> <td>ICAO / IATA Subrisk</td> <td>Not Applicable</td> </tr> <tr> <td>ERG Code</td> <td>1L</td> </tr> </table> | ICAO/IATA Class | 1.4G | ICAO / IATA Subrisk | Not Applicable | ERG Code | 1L |
| ICAO/IATA Class | 1.4G | | | | | | |
| ICAO / IATA Subrisk | Not Applicable | | | | | | |
| ERG Code | 1L | | | | | | |
| Packing group | Not Applicable | | | | | | |
| Environmental hazard | Not Applicable | | | | | | |

Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade

| | | |
|-------------------------------------|---|-----------|
| Special precautions for user | Special provisions | A132 |
| | Cargo Only Packing Instructions | 130 |
| | Cargo Only Maximum Qty / Pack | 75 kg |
| | Passenger and Cargo Packing Instructions | Forbidden |
| | Passenger and Cargo Maximum Qty / Pack | Forbidden |
| | Passenger and Cargo Limited Quantity Packing Instructions | Forbidden |
| | Passenger and Cargo Limited Maximum Qty / Pack | Forbidden |

Sea transport (IMDG-Code / GGVSee)

| | | |
|-------------------------------------|--|----------------|
| UN number | 0303 | |
| UN proper shipping name | AMMUNITION, SMOKE with or without burster, expelling charge or propelling charge | |
| Transport hazard class(es) | IMDG Class | 1.4G |
| | IMDG Subrisk | Not Applicable |
| Packing group | Not Applicable | |
| Environmental hazard | Not Applicable | |
| Special precautions for user | EMS Number | F-B , S-X |
| | Special provisions | 204 |
| | Limited Quantities | 0 |

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

9,10-ANTHRAQUINONE(84-65-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

| | |
|--|---|
| Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals | IMO IBC Code Chapter 17: Summary of minimum requirements |
| Australia Inventory of Chemical Substances (AICS) | IMO MARPOL (Annex II) - List of Noxious Liquid Substances Carried in Bulk |
| GESAMP/EHS Composite List - GESAMP Hazard Profiles | International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs |

POTASSIUM CHLORATE(3811-04-9) IS FOUND ON THE FOLLOWING REGULATORY LISTS

| | |
|--|---|
| Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 2 |
| Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5 |
| Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals | International Air Transport Association (IATA) Dangerous Goods Regulations |
| Australia Inventory of Chemical Substances (AICS) | International Maritime Dangerous Goods Requirements (IMDG Code) |
| Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2) | United Nations Recommendations on the Transport of Dangerous Goods Model Regulations |
| Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Index | |

SUCROSE(57-50-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

| | |
|------------------------------|---|
| Australia Exposure Standards | Australia Inventory of Chemical Substances (AICS) |
|------------------------------|---|

MAGNESIUM CARBONATE HYDROXIDE(7760-50-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

| | |
|--|---|
| Australia Inventory of Chemical Substances (AICS) | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 10 / Appendix C |
| Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2) | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5 |
| Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3) | Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6 |
| Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Index | |

POTASSIUM NITRATE(7757-79-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

| | |
|--|--|
| Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List | International Air Transport Association (IATA) Dangerous Goods Regulations |
| Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes | International Maritime Dangerous Goods Requirements (IMDG Code) |
| Australia Inventory of Chemical Substances (AICS) | United Nations Recommendations on the Transport of Dangerous Goods Model Regulations |
| Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2) | |

SILICON(7440-21-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

| | |
|------------------------------|---|
| Australia Exposure Standards | Australia Inventory of Chemical Substances (AICS) |
|------------------------------|---|

NITROCELLULOSE(9004-70-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List
 Australia Dangerous Goods Code (ADG Code) - Goods Too Dangerous To Be Transported
 Australia Explosives Code (AE Code)
 Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
 Australia Inventory of Chemical Substances (AICS)
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix A

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Index
 International Air Transport Association (IATA) Dangerous Goods Regulations
 International Air Transport Association (IATA) Dangerous Goods Regulations - Prohibited List Passenger and Cargo Aircraft
 International Maritime Dangerous Goods Requirements (IMDG Code)
 United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

ACETONE(67-64-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List
 Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes
 Australia Exposure Standards
 Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
 Australia Inventory of Chemical Substances (AICS)
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)
 Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Index

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5
 GESAMP/EHS Composite List - GESAMP Hazard Profiles
 IMO IBC Code Chapter 17: Summary of minimum requirements
 IMO IBC Code Chapter 18: List of products to which the Code does not apply
 IMO MARPOL 73/78 (Annex II) - List of Other Liquid Substances
 International Air Transport Association (IATA) Dangerous Goods Regulations
 International Maritime Dangerous Goods Requirements (IMDG Code)
 United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

NICKEL(7440-02-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards
 Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
 Australia Hazardous chemicals which may require Health Monitoring

Australia Inventory of Chemical Substances (AICS)
 International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

National Inventory Status

| National Inventory | Status |
|-------------------------------|--|
| Australia - AICS | Yes |
| Canada - DSL | Yes |
| Canada - NDSL | No (sucrose; magnesium carbonate hydroxide; acetone; nitrocellulose; silicon; nickel; 9,10-anthraquinone; potassium chlorate; potassium nitrate) |
| China - IECSC | Yes |
| Europe - EINEC / ELINCS / NLP | No (nitrocellulose) |
| Japan - ENCS | No (sucrose; silicon; nickel) |
| Korea - KECI | Yes |
| New Zealand - NZIoC | Yes |
| Philippines - PICCS | Yes |
| USA - TSCA | Yes |
| Taiwan - TCSI | Yes |
| Mexico - INSQ | No (magnesium carbonate hydroxide) |
| Vietnam - NCI | Yes |
| Russia - ARIPS | No (magnesium carbonate hydroxide) |
| Thailand - TECl | No (magnesium carbonate hydroxide) |
| Legend: | Yes = All CAS declared ingredients are on the inventory No = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets) |

SECTION 16 OTHER INFORMATION

| | |
|----------------------|---------------|
| Revision Date | 05/03/2017 |
| Initial Date | Not Available |

SDS Version Summary

| Version | Issue Date | Sections Updated |
|---------|------------|--|
| 2.1.1.1 | 10/08/2016 | Classification |
| 3.1.1.1 | 05/03/2017 | Classification, Fire Fighter (extinguishing media), Fire Fighter (fire/explosion hazard), Fire Fighter (fire incompatibility), First Aid (swallowed) |

Other information

Ingredients with multiple cas numbers

| Name | CAS No |
|-------------------------------|--|
| magnesium carbonate hydroxide | 7760-50-1, 12072-90-1 |
| silicon | 7440-21-3, 152284-21-4, 157383-37-4, 160371-18-6, 17375-03-0, 71536-23-7, 72516-01-9, 72516-02-0, 72516-03-1, 90337-93-2 |

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Combined Systems Model 5210B Baffled Pyrotechnic Smoke Grenade**Definitions and abbreviations**

PC—TWA: Permissible Concentration-Time Weighted Average
PC—STEL: Permissible Concentration-Short Term Exposure Limit
IARC: International Agency for Research on Cancer
ACGIH: American Conference of Governmental Industrial Hygienists
STEL: Short Term Exposure Limit
TEEL: Temporary Emergency Exposure Limit,
IDLH: Immediately Dangerous to Life or Health Concentrations
OSF: Odour Safety Factor
NOAEL :No Observed Adverse Effect Level
LOAEL: Lowest Observed Adverse Effect Level
TLV: Threshold Limit Value
LOD: Limit Of Detection
OTV: Odour Threshold Value
BCF: BioConcentration Factors
BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.